





LampFree® **Projectors**

Casio Laser & LED Hybrid Light Source













3100 LUMENS • WXGA (1280 X 800) NATIVE RESOLUTION ULTRA SHORT THROW 0.28:1 RATIO • FIXED LENS-MIRROR SYSTEM HYBRID LIGHT SOURCE
 DUST RESISTANT
 MADE IN JAPAN



Ultra Short Throw Lens

With its Ultra-Short Throw lens the XJ-UT310WN can project brilliant, shadow – free images up to 100" diagonal. The builtin short throw lens and advanced mirror system provides an extremely close throw ratio (0.28:1) and enables you to project an 80" image from just 1.5 feet away.

Brightness and Resolution

The XJ-UT310WN's advanced LampFree® light source combined with the Ultra-Short Throw lens system produces 3100 lumens of brightness and boast WXGA (1280 x 800) resolution which is ideal for displaying HD content from video and computer sources. The 16:10 widescreen aspect ratio ensures your content is viewed without distortion.

Connectivity

The XJ-UT310WN boasts a full suite of inputs including, Video, Computer and HDMI terminals with audio. It is equipped with a powerful 16 watt speaker and a dedicated dynamic microphone input ensures everyone can hear. Network (RJ-45) and local RS-232 connections provide control and remote status monitoring capabilities while close captioning used in conjunction with Crestron RoomView® allow direct email alerts and much more.

There is even 2GB of built-in memory storage for direct playback and viewing with the need for additional equipment. A CASIO App is also available and enables wireless connection and interaction with mobile devices.

CASIO App


Using CASIO's free mobile application – compatible with both Apple and Android – educators can easily integrate technology into the classroom. The mobile application allows educators to display and annotate presentations from a mobile device, as well as capture and save their work. In addition, educators can open an Internet browser and display content in real-time. There is also an image capture function using the mobile device's camera to snap an image and send it to the projector.

Superior Color

Hybrid light sources means an increased color range with projectors showing approximately 50% more of the spectrum for accurate renditions, subtle shadings and brighter images.

LampFree Benefits:

- Laser & LED Hybrid Light Source
- Mercury Free
- Quick Start (8 seconds to full brightness)
- Instant Off no cool down required
- 20,000 hour operating life
- No Lamp Replacement
- No Down Time
- Low Power Consumption
- Intelligent Brightness Control



© 2014 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA and WXGA are registered trademarks of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. MobiShow is a registered trademark of Awind Inc. iPhone, iPad and iPod are registered trademarks of Apple Inc. Android is a trademark of Google Inc. Other product names or company names on this specification brochure are either



^{*} Extended Use Applications are defined as operation of 10 hours per day for 5 or more days per week. Under these conditions the light source warranty is one (1) year or 6000 hours.



Casio Projector	Ultra Short Throw: XJ-UT310WN
Specifications	WXGA
Native Resolution	1280 x 800 • 1,024,000 pixels
Native Aspect Ratio	16:10
Brightness	3100
Display Device	0.65" DLP® chip
Contrast Ratio	1800:1
Lens Type Lens Offset	Fixed Zoom/Manual Focus Mirror System (F2.3/f4.2) TBD
Light Source	Casio Laser & LED Hybrid
Estimated Light Source Life	Up to 20,000 Hours
Projection Screen Size (Min-Max)	50" ~110" (diagonal)
Projection Range	40.0"
77" w screen	18.8" 21.5"
87" w screen Minimum	50"
Throw Ratio	0.28:1
Keystone Correction	0.26.1 Manual +/- 5°
Color Reproduction	Full color (16.77 million colors)
Power Source	AC100~240V, 50/60Hz
Power Consumption	TOTAL ETOTI SOLOTILE
Operating	230 watts Eco Mode "Off" Bright Selected, 110 watts Eco Mode 5
Standby	0.12W (LAN Off), 0.23W (LAN On)
TERMINAL CONNECTIVITY	
Video Signal Compatibility Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
Video Systems DTV/HDTV	NTSC/ PAL/ PAL-N/ PAL-N/ PAL60/ SECAN 480i/480P/576i/576P/720P/1080i/1080p
Maximum Computer Input	4ου/4ου/30/70/720/710ου/10ουμ UXGA (1600 x 1200)
INPUTS	orton (1000 in 1200)
RGB/Component Video Input	mini D-Sub 15 pin x 2 ● Also use as YCbCr/YPbPr input — commercially available adapter required
HDMI	HDMI Type A x 1 (480p~1080p, HDCP support, audio signal support)
Composite Video/Audio	Composite Video (RCA) x 1, S-Video x 1/RCA (R/L) x1, Stereo mini x 2
USB	Type A (USB 2.0) x 1/Type B x 1
USB Display Port	Yes
Micro USB	Yes (for logo data upload)
Built-in Memory	Yes ● 2 GB (PDF, JPEG, BMP, PNG, GIF, AVI (MJPEG video, ADPCM audio), MOV (H.264 video, ADPCM audio or AAC audio), MP4 (H.264 video, AAC audio), ECA, PtG)
Microphone	3.5 mm Mini jack (Dynamic Microphone compatible)
Wireless Capability	Wireless LAN Adapter (YW-40) is included with USB Models (802.11 b/g/n)
	Wilcless Env Adapter (1W 40) is included with 050 Models (002.11 b/g/ii)
OUTPUTS	
	3.5 mm Mini - Stereo ● Variable Audio
Audio	3.5 mm Mini - Stereo ● Variable Audio Mini D-sub 15 pin x 1
Audio RGB Output AUDIO AND CONTROL SYSTEMS	Mini D-sub 15 pin x 1
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system	
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal	Mini D-sub 15 pin x 1 16W Monuaural Speaker
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T)
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T)
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation)
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (not condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes ● Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes ◆ Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty)	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes of Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors MA x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=1&cid=007&pid=1158
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Fare Download http://support.casio.com/download.php?rgn=1&cid=007&pid=1158 YM-80 Wall Mount
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes of Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors MA x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=1&cid=007&pid=1158
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Fee Download http://support.casio.com/download.php?rgn=1&cid=007&pid=1158 YM-80 Wall Mount
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color Dimension (W x D x H)	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=1&cid=0078pid=1158 YM-80 Wall Mount White/Gray
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color Dimension (W x D x H) Including Terminal Cover Excluding Terminal Cover Weight	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=1&cid=007&pid=1158 YM-80 Wall Mount White/Gray 16.3 x 13.1 x 6.0
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color Dimension (W x D x H) Including Terminal Cover Excluding Terminal Cover Weight	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes * Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=1&cid=007&pid=1158 YM-80 Wall Mount White/Gray 16.3 x 13.1 x 6.0 13.3 x 13.1 x 6.0
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color Dimension (W x D x H) Including Terminal Cover Excluding Terminal Cover Weight Packing Information Carton Dimensions	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=18cdi=007&pid=1158 YM-80 Wall Mount White/Gray 16.3 x 13.1 x 6.0 13.3 x 13.1 x 6.0 12.54 lbs 23.4" x 18.5" x 10.8"
Audio RGB Output AUDIO AND CONTROL SYSTEMS Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color Dimension (W x D x H) Including Terminal Cover Excluding Terminal Cover Weight Packing Information Carton Dimensions Carton Dimensions Carton Weight	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41,~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete detail: Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=18cid=007&pid=1158 YM-80 Wall Mount White/Gray 16.3 x 13.1 x 6.0 12.54 lbs 23.4" x 18.5" x 10.8" 28.6 lbs
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temperature Operating Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws (Type x Qty) Limited Warranty Included Accessories Included Software USB Models Only Windows® Compatible Only Optional Accessories Cabinet Color Dimension (W x D x H) Including Terminal Cover Excluding Terminal Cover Weight Packing Information Carton Dimensions	Mini D-sub 15 pin x 1 16W Monuaural Speaker RS-232C (Mini D-sub 9 pin) x 1 RJ-45 x 1 (100 BASE-TX/10 BASE-T) AMX, Crestron, Extron, SP Controls 41~95°F 20~80% (non condensation) Yes (for operation 4,900~9,800 ft) Yes • Note: Projector must be turned off once every 24 hours No Yes 16.5 ft Maximum Kensington™ Compatible/Power On Password/Secruity Bar Compatible with "Universal" Mounts, sold separately by 3rd party vendors M4 x 4 (not included) Depth 8 mm 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details Wireless remote control, YW-40 Wireless adapter, Terminal Cover, 6' RGB Cable, 6' AC Power cord, Setup Manual (Printed) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3 for CASIO Projector Note: Mac Compatible Wireless software (wePresent) available as a Free Download http://support.casio.com/download.php?rgn=18cd=007&pid=1158 YM-80 Wall Mount White/Gray 16.3 x 13.1 x 6.0 13.3 x 13.1 x 6.0 12.54 lbs 23.4" x 18.5" x 10.8"

