

BenQ

MX710/711

Digital Projector



HIGHLIGHTS

- Microphone in with 10W speaker x 1
- USB reader
- USB Display (Plug-n-Play)
- LAN Display
- 4-1 Display
- Remote Desktop
- Wireless Display (Optional)
- Crestron RoomView compatible
- PJ-Link compatible
- 2700/3200 ANSI Lumens
- XGA Native Resolution
- BrilliantColor™
- 3D Color Management
- VIDITM
- Vertical Auto Keystone
- Keystone ± 40 Degree
- 6 Segment color wheel
- Variable Audio Out
- Closed Captioning

| | | |
|-----------------------------|--|---|
| Projection System | DLP® technology by Texas Instruments® | |
| Native Resolution | XGA (1024 x 768) | |
| Brightness | 2700/3200 ANSI lumens | |
| Contrast Ratio | 5300:1 (Full on/Full off) | |
| Keystone | Auto Keystone Vertical ± 40 Degree; Manual Vertical ± 40 Degree | |
| Aspect Ratio | 4:3 Native (5 selectable aspect ratio) | |
| Color | Full 16.7 million color palette | |
| Lens | F=2.59~2.87 | |
| Zoom Ratio | Manual Zoom, 1.3:1 | |
| Image Size (Diagonal) | 32" to 300" | |
| Throw Ratio | 1.5 to 1.97(65"@2M) | |
| Lamp | 210W, 4000/5000 hrs ; 230W 3500/5000hrs(Normal/Economic mode) | |
| Computer Compatibility | VGA to UXGA | |
| HDTV Compatibility | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p | |
| Video Compatibility | NTSC, PAL, SECAM | |
| Horizontal Frequency | 31-92 kHz | |
| Vertical Scan Rate | 48-120 Hz | |
| Input Terminals | PC | Analog RGB: D-sub 15 pin x 2 LAN Networking: RJ-45 x1 (LAN Display) USB connector: Type A x 1 (USB thumb drive) USB Type mini B x1 (USB display) |
| | A/V | HDMI V1.3 x 1 S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 |
| | Audio | Audio L/R : RCA x 1(set) Stereo Mini Jack x 1 |
| Output Terminals | PC | D-sub 15 pin x 1 Variable Audio Out : Stereo Mini Jack x 1 |
| | Audio | 10W x 1 |
| Control Terminal | Serial Connector : RS232 x 1 | |
| | RJ45 x 1 USB mini Type B x 1(Page up/down) shared | |
| Dimensions(W x H x D) | 311 x 104 x 244 mm | |
| Weight | 2.7kg | |
| Power Supply | 100 to 240 VAC, 50/60 Hz | |
| Power Consumption | 286/306W, Standby < 1W | |
| Audible Noise | 30/26 dBA; 32/27dBA (Normal/Economic mode) | |
| On-Screen Display Languages | Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/ Indonesian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (26 Languages) | |
| Picture Modes | PC Input: | A/V Input : |
| | Dynamic Mode | Dynamic Mode |
| | Presentation Mode | Presentation Mode |
| | sRGB Mode | sRGB Mode |
| | Cinema Mode | Cinema Mode |
| | User 1 Mode | User 1 Mode |
| Functions | User 2 Mode | User 2 Mode |
| | BrilliantColor™ | Blank |
| | VIDITM | Panel Key Lock |
| | 3D Color Management | Auto Off |
| | Crestron LAN Control | Security Password |
| | Closed Captioning | HDTV Compatible |
| | Digital Zoom (x2) | High Altitude Mode |
| | Variable Audio Out | "Q?" Hot Key for FAQ |
| | Quick Cooling | 3D Ready |
| | Quick Auto Search | Freeze |
| Accessories (Standard) | Quick Start Guide | VGA(D-sub) cable |
| | Manual CD | Power cord |
| | Remote control w/battery | Soft carry case |
| Accessories (Optional) | Presentation Plus | Spare Lamp Kit |
| | RS232 Cable | Wireless Dongle |