

NEC M362W

Order Code: 60003577

NEC M362W Professional Desktop Projector

The excellent price performance ratio makes this projector especially suitable for classrooms and mid sized meeting rooms. The filter free design with dust-protected DLP light engine, very long lamp life and low power consumption results into remarkably low cost of ownership. Various innovative new ECO functions such as the Ambient Light Sensor help to significantly reduce power consumption.

The Free DisplayNote Presenter licence adds the possibility for interactive, mobile presentation with tablets.



DELIVERING GENUINE BENEFITS

Maximum Flexibility - due to large 1.7x optical zoom, horizontal and vertical keystone correction.

Robust and dust resistant - thanks to sealed DLP light engine.

Low cost of ownership - up to 8000h lamp life, low power consumption.

Great connectivity - due to numerous analog and digital connection terminals as well as network capability.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.

OUTSTANDING PERFORMANCE

- Large 1.7x optical zoom
- Horizontal and vertical keystone correction
- Filter free design with sealed DLP light engine
- Long lamp life up to 8000h
- Ambient Light Sensor and Auto ECO Mode
- Powerful 20W speaker



SPECIAL CHARACTERISTICS

Ambient Light Sensor, Auto Eco Mode, Auto Power-ON Function, Carbon Savings Meter, Colour Management, Constant Brightness Mode, Content Transmission via Network, Crestron RoomView, DICOM Simulation, Full 3D DLP ® LINK support, High Altitude Mode, Kensington security slot, Keypad Lock, Magnify, NaViSet Administrator 2, Optional User Logo, Optional WLAN, OSD with 29 languages, Password Security System, Quick Start, Remote control and administration via LAN and RS232, Security Bar, USB Viewer for JPEG, Virtual Remote for direct PC control, Wall Colour Correction



Energy Efficiency 75% AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; ImageCare® Technology; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling

Ecological Materials 100% recyclable packaging; Downloadable manuals; ECO packaging

Ecological Standards ErP compliant; RoHS compliant

Technical Specification NEC M362W

| | |
|--------------------------------------|---|
| IMAGE | |
| Projection Technology | 1 x 1.65 cm (0.65") 2x LVDS DMD Chip |
| Native Resolution | 1280 x 800 (WXGA) |
| Aspect Ratio | 16:10 |
| Contrast Ratio ¹ | 10000:1 |
| Brightness ¹ | 3600 ANSI Lumen (approx. 75% in Eco Mode) |
| Lamp | 250 W AC (150 W AC Eco Mode) |
| Lamp Life [hrs] | 3500 (8000 Eco Mode) |
| Lens | F= 2.4–3.1, f= 17.09–29.05 mm |
| Keystone correction | +/- 25° manual horizontal / +/- 30° automatic / manual vertical |
| Projection Factor | 1.2 – 2.04 : 1 |
| Projection Distance [m] | 0.76 – 13.53 |
| Projection Angle [°] | 10.5 - 17.6 |
| Screen Size (diagonal) [cm] / [inch] | 76.2 / 30" - 762 / 300" |
| Zoom | Manual |
| Focus Adjustment | Manual |
| Supported Resolutions | 1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1680 x 1050 (WSXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA+); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (Maximum resolution of digital input); 1280 x 1024 (SXGA); 1280 x 1024 (MAC 23"); 1280 x 960 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 576 (DVD progressive); 720 x 480 SDTV 576p/576i; 720 x 480 (SDTV 480p); 640 x 480 (VGA/MAC 13") |
| Frequency | Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz |
| CONNECTIVITY | |
| RGB (analog) | Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin |
| HDMI™ | Input: 2 x HDMI™ (Deep Color, Lip sync) |
| Video | Input: 1 x RCA |
| Audio | Input: 1 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable) |
| Microphone | Input: 1 x 3.5 mm Monaural Mini Jack (Dynamic mic / Condenser mic) |
| Control | Input: 1 x D-Sub 9 pin (RS-232) (male) |
| LAN | 1 x RJ45; Optional WLAN |
| USB | 1 x Type A (USB 2.0 high speed); 1 x Type B |
| 3D Sync | Output: 1 x Mini DIN 3pin |
| Video Signals | NTSC; NTSC 4.43; PAL; PAL-M; PAL60; SECAM |
| REMOTE CONTROL | |
| Remote Control | Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Optional Presentation and Mouse Control; Picture Adjust; Source Select |
| ELECTRICAL | |
| Power Supply | 100-240 V AC; 50 - 60 Hz |
| Power Consumption [W] | 244 (Normal) / 224 (Eco) / 2.9 (Network Stand-by) / 0.4 (Stand-by); 315 (High Bright) |
| MECHANICAL | |
| Dimensions (W x H x D) [mm] | 367.9 x 97.5 x 285.9 (without lens and feet) |
| Weight [kg] | 3.6 |
| Fan Noise [dB (A)] | 33 / 33 / 37 (ECO / Normal / High Bright) |
| ENVIRONMENTAL CONDITIONS | |
| Operating Temperature [°C] | 5 to 40 |
| Operating Humidity [%] | 20 to 80 |
| Storage Temperature [°C] | -10 to 50 |
| Storage Humidity [%] | 20 to 80 |
| ERGONOMICS | |
| Safety and Ergonomics | CE; EAC; Gost-R; RoHS |
| Speakers [W] | 1 x 20 (mono) |
| WARRANTY | |
| Projectors | 3 years pan-European service |
| Lamp | 6 months, max. 1000 hrs |
| SHIPPING CONTENT | |
| Shipping Contents | IR Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM |
| OPTIONAL ACCESSORIES | |
| Optional Accessories | Adapter for Intel WIDI (NP01WR); DisplayNote: DLP-Link 3D Glasses (NP02GL); Lamp (NP29LP); Wireless LAN module (NP02LM2 for EU, NP02LM3 for Russia) |

¹ Compliance with ISO21118-2005