

MC342X

Professional Desktop Projector

# **Datasheet**





#### **Performance Projection with low TCO**

Delivering reliable visual support for successful lectures and presentations, the compact multipurpose MC Series delivers crisp projected images and natural colours to your classroom or meeting facility thanks to LCD technology. The second generation comes with a 1.0A powered USB to power external devices without the need for an additional power plug. Comprehensive connectivity with 4K@ 30Hz input processing and optional WiFi provide utmost flexibility and time saving operation. The preinstalled and enhanced MultiPresenter function enables simultaneous wireless presenting and sharing for up to 16 devices when the optional WiFi is chosen. The second generation comes with an even longer lamp life of 10,000 hrs in normal mode for smooth operation over a time period of over 9 years\*. Thank to this improvement, you can enjoy lower maintenance saving you time and cost. Furthermore, with noise levels of only 29 dB in eco mode, there is no disturbance during your presentation.

st at 8 hours operation a day, 200 days a year

#### **Benefits**

Minimized cost of ownership - due to long lamp life and filter exchange intervals.

Versatile and mobile - compact and light-weight with HDMI and integrated 16W speaker.

**Display content that demands attention** - with XGA resolution and superb brightness levels and colour ranges, your viewers will enjoy an outstanding visual experience.

**Cost effective replacement** – of existing NEC M LCD model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

Future-proof input management - thanks to 4K@30 Hz input processing.

**Wide array of flexible application scenarios** – thanks to multi-source conferencing and efficient split-screen operation supported by a wide future-ready range of digital connectivity.

Product Information	
Product Name	MC342X
Product Group	Professional Desktop Projector
Order Code	60004705
Image	
Projection Technology	3LCD Technology
Native Resolution	1024 x 768 (Value)
Aspect Ratio	4:3
Contrast Ratio <sup>1</sup>	16000:1
Brightness <sup>1</sup>	3400 Normal / 2300 Eco ANSI Lumen; 3700 Centre Lumen
Lamp	225 W AC (151 W AC Eco Mode)
Light Source Life [hrs]	10000 (15000 Eco Mode)
Lens	F= 2.1-2.25, f= 19.1-22.9 mm
Keystone correction	+/- 30° manual horizontal / +/- 30° manual vertical
 Projection Angle [°]	8.6 - 10.3
Projection Factor	1.5 - 1.8 : 1
Projection Distance [m]	0.89 - 10.94
Screen Size (diagonal) [cm] / [inch]	Maximum: 762 / 300"; Minimum: 76 / 30"
Zoom	Manual; x1.2
Focus Adjustment	Manual
Supported Resolutions	3840x2160 @ 30hz digital; 1024x768 (Maximum resolution of analog input)
Frequency	Horizontal: 15-100 kHz (RGB: 24 kHz- 100 kHz); Vertical: 50 - 120 Hz
Connectivity	
RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
 Digital	Input: 2 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
Audio	Input: 1 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45; Optional WLAN
USB	1 x Type A (USB 2.0 high speed); 1 x Type B
Video Signals	NTSC; PAL; PAL60; SECAM
Remote Control	
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Optional Presentation and Mouse Control; Picture Adjust; Picture Mode; Source Select
Electrical	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	288 (High Bright) / 196 (Eco) / 1.5 (Network Stand-by) / 0.5 (Stand-by)
Mechanical	
Dimensions (W x H x D) [mm]	345 x 104.6 x 261 (without lens and feet)
Weight [kg]	3.1

-n	viron	menta	31 <i>(</i> 0	MAIT	nnc

Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80

# **Ergonomics**

Safety and Ergonomics	CE; EAC; ErP; RoHS; TUEV Type Approved; WEEE
Speakers [W]	1 x 16 (mono)

# **Additional Features**

Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Colour Management; Content
Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function;
High Altitude Mode; Kensington security slot; Keypad Lock; Keystone Correction (H=±30°,
V=±30°); Lens Cover; Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo;
Optional WLAN; OSD with 29 languages; Password Security System; Quick On/Off; RS-232
Control; Security Bar; USB Display; USB Viewer for JPEG; Virtual Remote for direct PC control;
Wall Colour Correction

#### **Green Features**

Energy Efficiency	75 % AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; Intelligent Power Management; Longer Light Source Life; Reduced power consumption. Only 0.45W stand-by; Software scheduling
Ecological Materials	100% recyclable packaging; Downloadable manuals; ECO packaging
Ecological Standards	ErP compliant; RoHs compliant; WEEE

# Warranty

Projectors	3 years pan-European service
Light Source	6 months, max. 1000 hrs

# **Shipping Content**

Shipping Contents	IR Remote Control (RD-469E); Mini D-SUB Signal Cable (1.8 m); Quick Setup Guide; Security
	Sticker; Users Manual on CD-ROM; Utility software

#### **Optional Accessories**

Optional Accessories	
Optional Accessories	Lamp (NP47LP); MultiPresenter Stick; Universal Ceiling Mounts (PJ01UCM); Wireless LAN
	module NP05LM2 (Europe), NP05LM4 (Russia)

 $<sup>^{1}</sup>$  Compliance with ISO21118-2012







CE





RoHS

This document is © 2020 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 07.10.2020



For, more information contact:

Projector Square

+971 4 3300429

info@projectorsquare.com | www.projectorsquare.com

